


Specification : SS 400 / S275

MM Width	INCHES	THK	Kg / 6 m
12MM	1/2	3.0mm	1.70
		6.0mm	3.42
15MM		3.0mm	2.12
		4.0mm	2.83
		4.5mm	3.18
		6.0mm	4.24
16MM	5/8	3.0mm	2.262
		4.5mm	3.39
		6.0mm	4.524
18MM		3.0mm	2.54
		4.0mm	3.39
		4.5mm	3.82
		6.0mm	5.09
		9.0mm	7.63
19MM	3/4	3.0mm	2.682
		4.5mm	4.02
		6.0mm	5.37
		9.0mm	8.04
25MM	1	3.0mm	3.534
		4.0mm	4.71
		4.5mm	5.28
		5.0mm	5.89
		6.0mm	7.07
		8.0mm	9.42
		9.0mm	10.62
		12.0mm	14.16
32MM	1-1/4	3.0mm	4.524
		4.5mm	6.78
		6.0mm	9.06
		8.0mm	12.06
		9.0mm	13.56
		12.0mm	18.08
38MM	1-1/2	3.0mm	5.37
		4.5mm	8.05
		6.0mm	10.74
		8.0mm	14.34
		9.0mm	16.08
		12.0mm	21.48
		16.0mm	28.62
44MM	1-3/4	6.0mm	12.43
		9.0mm	18.66
		12.0mm	24.87
50MM	2	3.0mm	7.08
		4.5mm	10.62
		6.0mm	14.16
		8.0mm	18.84
		9.0mm	21.2
		12.0mm	28.26
		16.0mm	37.68
		19.0mm	44.76
25.0mm	58.86		



**F
L
A
T

B
A
R**



MM Width	INCHES	THK	Kg / 6 m
65MM	2-1/2	3.0mm	9.18
		4.5mm	13.80
		6.0mm	18.36
		8.0mm	24.49
		9.0mm	27.55
		12.0mm	36.72
		16.0mm	48.96
		19.0mm	58.14
75MM	3	25.0mm	76.80
		3.0mm	10.60
		4.5mm	15.60
		6.0mm	21.18
		8.0mm	28.26
		9.0mm	31.80
		12.0mm	42.36
100MM	4	16.0mm	56.52
		19.0mm	67.20
		25.0mm	88.30
		6.0mm	28.26
		8.0mm	37.68
		9.0mm	42.39
125MM	5	12.0mm	56.52
		16.0mm	75.60
		19.0mm	89.50
		25.0mm	117.6
		6.0mm	35.34
150MM	6	8.0mm	47.1
		9.0mm	52.98
		12.0mm	70.8
		16.0mm	94.2
200MM	8	19.0mm	111.87
		25.0mm	147.20
		6.0mm	42.39
		8.0mm	56.52
		9.0mm	63.6
250MM	10	12.0mm	84.78
		16.0mm	113.04
		19.0mm	134.4
		25.0mm	176.6
300MM	12	6.0mm	56.52
		9.0mm	84.78
		12.0mm	113.04
		16.0mm	150.6
		19.0mm	178.8
250MM	10	25.0mm	235.5
		6.0mm	70.68
		9.0mm	106.2
		12.0mm	141.6
		16.0mm	188.4
		19.0mm	223.8
300MM	12	25.0mm	294.38
		6.0mm	84.78
		9.0mm	127.2
		12.0mm	169.8
		16.0mm	226.2
300MM	12	19.0mm	268.47
		25.0mm	353.25

Thickness Tolerance : ± 10%