



## U-Channel

( Tapered / Parallel Flanges )  
Specification : SS 400



## Lip Channel ( Purlin )

SIZES D X B		
MM / INCHES	THK	KG / 6M
50 x 25 ( 2" x 1" )	4.0mm	17.52
75 x 40 ( 3 x 1-1/2 )	3.8mm	31.8
	4.0mm	33.6
	4.5mm	35.1
	5.0mm	41.52
100 x 50 ( 4 x 2 )	3.8mm	43.8
	4.2mm	48.18
	4.5mm	53.82
	5.0mm	56.16
125 x 65 ( 5 x 2-1/2 )	5.2mm	69.96
	5.5mm	77.46
	6.0mm	80.4
150 x 75 ( 6 x 3 )	5.5mm	87.96
	6.0mm	108.06
	6.5mm	111.6
180 x 70	8.0mm	132
	7.0mm	128.4
200 x 75 ( 8 x 3 )	8.0mm	181.8
200 x 80	7.5mm	147.6
200 x 90 ( 8 x 3-1/2 )	8.0mm	181.8
250 x 90 ( 10 x 3-1/2 )	9.0mm	207.6
	9.0mm	228.6
300 x 90 ( 12 x 3-1/2 )	10.0mm	262.8
	10.5mm	281
380 x 100 ( 15 x 4 )	10.5mm	327
	13.0mm	372

JIS: G3350 & SS104 Specification

SIZES H x A x C		
MM / Inches		
MM / INCHES	THK	KG/6M
60 x 30 x 10	1.6mm	9.78
	2.3mm	13.5
75 x 45 x 15 ( 3 x 1-3/4 x 3/5 )	1.6mm	13.92
	2.0mm	17.16
	2.3mm	19.5
	3.0mm	24.78
100 x 50 x 20 ( 4 x 2 x 3/4 )	2.3mm	24.36
	3.0mm	31.14
	3.2mm	33.00
	4.0mm	40.26
	4.5mm	44.58
125 x 50 x 20 ( 5 x 2 x 3/4 )	2.3mm	27.06
	3.0mm	34.68
	3.2mm	36.78
	4.0mm	45.00
	4.5mm	49.92
150 x 65 x 20 ( 6 x 2-1/2 x 3/4 )	2.3mm	33.00
	3.0mm	42.42
	3.2mm	45.06
	4.0mm	55.32
	4.5mm	61.80
175 x 75 x 20 ( 7 x 3 x 3/4 )	2.3mm	37.92
	3.0mm	48.78
	3.2mm	51.78
	4.0mm	63.78
	4.5mm	71.04
200 x 75 x 20 ( 8 x 3 x 3/4 )	2.3mm	40.56
	3.0mm	52.26
	3.2mm	55.62
	4.0mm	68.4
	4.5mm	76.38

Thickness Tolerance : ± 10%

Thickness Tolerance : ± 10%